







Ambient Light Rejecting Screens

Series Name	Starling Tab-Tension 2 CineGrey 5D®	Sable Frame CineGrey 3D®	ezFrame CineGrey 5D®	Aeon CineGrey 3D®	Aeon CLR®	WhiteBoardScreen
Product Picture						
Suggested Applications	Conference Rooms, Boardrooms, Family/Living/Media Rooms, Home Theater, Sports Bars, Game Rooms, House of Worship, Training facilities	Family/Living/Media Rooms, Home Theater, Conference Rooms, Boardrooms, Training facilities, Sports Bars, Game Rooms, House of Worship	Family/Living/Media Rooms, Home Theater, Game Rooms, Sports Bars, Conference Rooms, Boardrooms, Training facilities, House of Worship	Family/Living/Media Rooms, Home Theater, Game Rooms, Sports Bars, Conference Rooms, Boardrooms, Training facilities, House of Worship	Family/Living/Media Rooms, Home Theater, Conference Rooms, Boardrooms, Training facilities, Game Rooms	Classrooms, Conference rooms, Boardrooms, Training facilities, Lecture Halls
Screen Type	Electric/Motorized - Wall/Ceiling	Fixed Frame	Fixed Frame	EDGE FREE® Fixed Frame	EDGE FREE® Fixed Frame	Rigid WhiteBoardScreen
Compatible Projector Type	*Short and Standard-throw (*0.8 lens throw ratio or greater)	*Short and Standard-throw (*0.8 lens throw ratio or greater)	*Short and Standard-throw (*0.8 lens throw ratio or greater)	*Short and Standard-throw (*0.8 lens throw ratio or greater)	Ultra-Short Throw	Standard-throw

Screen Material	CineGrey 5D®	CineGrey 3D®	CineGrey 5D®	CineGrey 3D®	StarBright CLR®	StarBright 4
Gain	1.5	1.2	1.5	1.2	0.6	4.0
Viewing Angle	80° (40° L/R)	90° (45° L/R)	80° (40° L/R)	90° (45° L/R)	180° (90° L/R)	120° (60° L/R)
Diagonal Size and Aspect Ratio	16:9 - 92"/106"/120"/135"	16:9 - 100"/110"/120"/135"/150"	16:9 - 92"/100"/110"/120"/135"/150"/165"/180"/200"/235"	16:9 - 92"/100"/110"/120"/135"/150"	16:9 - 100"	4:3 - 60"
Reflection technology	Angular-Reflective	Angular-Reflective	Angular-Reflective	Angular-Reflective	Retro-Reflective	Angular-Reflective
Ceiling Ambient Light Rejection	75%	65%	75%	65%	95%	80%
Projection material type	Front Projection	Front Projection	Front Projection	Front Projection	Front Projection	Front Projection
Minimum lens throw ratio	0.8:1	0.8:1	0.8:1	0.8:1	0.3	1.5
Easy to clean	Yes	Yes	Yes	Yes	Yes	Yes
4K/8K Ultra HD Ready	Yes	Yes	Yes	Yes	Yes	Yes
3D compatible	Active/Passive	Active/Passive	Active/Passive	Active/Passive	Active	Active
GREENGUARD Certified	Yes	Yes	Yes	Yes	No	No
ISF Certified	Yes	Yes	Yes	Yes	No	No
Flame Retardant	Complies with NFPA 701	Complies with NFPA 701	Complies with NFPA 701	Complies with NFPA 701	N/A	N/A

Installation and Accessories						
Installation Method	Wall/Ceiling	Wall	Wall	Wall	Wall	Wall
Wall/Ceiling Brackets included	Yes	Wall only	Wall only	Wall only	Wall only	Wall only
Installation hardware kit included	Yes	Yes	Yes	Yes	Yes	Yes
Slideable brackets permit wood stud installation	Yes	Yes	Yes	Yes	Yes	Yes
Accessories Included	IR/RF remotes, 12 volt trigger, and IR extended sensor	N/A	N/A	N/A	Aluminum bezel trim and LED backlight kit	Dry-erase markers, eraser, pen tray
Housing/Frame color and type	Aluminum Black	Aluminum covered in black velvet	Aluminum covered in black velvet	Aluminum with option for thin edge bezel	Aluminum with option for thin edge bezel	Aluminum black matted frame
Motor type/speed	Tubular - Fast	N/A	N/A	N/A	N/A	N/A
Frame Width	N/A	2.4"	2.4"	EDGE FREE™	EDGE FREE™	1"