







In-Ceiling Recessed Motorized Retractable Projection Screens Comparison

Series Name	Evanesce B	Evanesce Tab-Tension B	Evanesce	Evanesce Tab-Tension	Evanesce Tab-Tension B CineGrey® 5D	Evanesce Plus B
Picture						
Applications	Home Cinema, Family Room, Training/Conference Room	Home Cinema, Family Room, Training/Conference Room	Home Cinema, Family Room, Training/Conference Room	Home Cinema, Family Room, Training/Conference Room	Home Cinema, Family Room, Training/Conference Room	Large Training/Conference Room/ Auditoriums
Recommended room size and lighting environment	Small to Medium - Light controlled	Small to Medium - Light controlled	Small, Medium, Large - Light Controlled	Small to Medium - Light Controlled	Small to Medium - Ambient Light cannot be controlled	Large - Light Controlled
Screen Material	MaxWhite® FG (matte white fiberglass reinforced)	CineWhite® (matte white tensioned)	MaxWhite® FG (matte white fiberglass reinforced) / AcousticPro AUHD (acoustically transparent)	CineWhite® (matte white tensioned)	CineGrey® 5D (ambient light rejecting)	MaxWhite® FG (matte white fiberglass reinforced)
Projector compatibility	Standard (long) throw only	Ultra, short, and standard throw	Standard (long) throw only	Ultra, short, and standard throw	Standard (long) throw only	Standard (long) throw only
Gain	1.1	1.1	1.1 / 1.0	1.1	1.5	1.1
Viewing Angle	180°	180°	180° / 180°	180°	80°	180°
Size and Aspect Ratio	16:9 - 92"/100"/110"/120" 4:3 - 100"/120"	16:9 - 92"/ 100"/ 120"	16:9 - 90"/ 106"/ 112"/ 126"/ 140"	4:3 - 100"/120" 16:9 - 100"/106"/120"/135" 16:10 - 126"	16:9 - 106"/126"	16:9 - 150"/180"/200"
4-sided black masking borders	Yes	Yes	Yes	Yes	Yes	Yes
Black Top Border Drop	8" - 12" varies by model	8" - 12" varies by model	6" - 24" varies by model	8"	12"	8" - 12" varies by model
Greenguard Certified	Yes	No	Yes	No	Yes	Yes
Flame Retardant	Complies with NFPA 701	N/A	Complies with NFPA 701	Complies with NFPA 701	Complies with NFPA 701	Complies with NFPA 701

Control System

Infrared Remote	Yes	Yes	Yes	Yes	Yes	Yes
Radio Frequency Remote	Yes	Yes	Yes	Yes	Yes	Yes
3-position wall switch	Yes	Yes	Yes	Yes	No	Yes
IR "eye" extended sensor	Yes	Yes	Yes	Yes	Yes	Yes
RJ45 input port	Yes	Yes	Yes	Yes	No	Yes
Wireless 5-12 volt trigger	Included	Included	Included	Included	Wired only	Included

Design and Installation

Housing Dimensions (WxH) in.	3.1" x 3.0"	3.1" x 3.0"	3.9" x 4.6"	3.9" x 4.6"	7.3"x6.1"	5.3" x 5.9"
Method of Installation	In-ceiling Recessed - Above and Below access	In-ceiling Recessed - Above and Below access	In-ceiling Recessed - Above and Below access	In-ceiling Recessed - Above and Below access	In-ceiling Recessed - Above and Below access	In-ceiling Recessed - Above access only
Installation kit included	Yes	Yes	Yes	Yes	Yes	Yes
Motor Type and speed	Tubular - 14 RPM	Tubular - 14 RPM	Tubular - 30 RPM	Tubular - 30 RPM	Tubular - 33 RPM	Tubular - 30 RPM
Noise Decibel	48 dB	48 dB	48 dB	48 dB	33 dB	48 dB
Plenum Rated	N/A	N/A	Yes	Yes	N/A	N/A

Suggested Retail Pricing (U.S. only)

From	\$504 - \$643	\$615 - \$814	\$879 - \$2,139	\$835 - \$1,308	\$1,429 - \$2,089	\$2,295 - \$3,711
------	---------------	---------------	-----------------	-----------------	-------------------	-------------------