



The **Home 2** premium grade electric projector screen has been acclaimed by our customers as an excellent example of a high end product that uses Elite's GREENGUARD® certified MaxWhite® FG fiberglass-backed multi layer screen material. In addition to its fast-acting tubular motor, this product comes with IR/RF remote controls, wall control unit with IR receiver and low-profile extended IR "Eye" receiver, 12V-Trigger port with attachment, simplified direct power connection, as well as floating wall brackets for a perfectly centered image.

Screen Material

- MaxWhite® FG backed material provides uniform flatness on a flat projected image
- 180° wide viewing angle
- 4K/8K Ultra HD, Active 3D, and HDR Ready
- Not compatible with Ultra/Short-throw Projectors
- Standard 4-side black masking borders
- Available in the following diagonal sizes:
 - 135" in 1:1 format
 - 90" and 135" in 4:3 format
 - 90", 100" and 135" in 16:9 format

Quality & Reliability

- Tubular motor allows swift operation with a superior weight tolerance and operational lifespan
- Certified by AMX and CRESTRON
- Conforms to ANSI/UL STD. 60950-1
- Certified to CAN/CSA STD. C22.2
- Flame Retardant: Complies with NFPA 701 Standards
- 2-year Parts & Labor manufacturer's warranty
- 3-year warranty offered through ENR-G program (Education, Non-Profit, Religious and Government)
- GREENGUARD® and GREENGUARD® Gold Certified | UL 2818

Design & Installation

- Floating installation brackets provide easy alignment with wood studs to accommodate a wall or ceiling installation
- Aluminum housing with enamel coating is moisture resistant
- Shipped ready to plug & play with installation kit containing brackets, screws, and bubble leveler included
- Optional in-ceiling trim kit - **sold separately**
- Optional extended 11x4 or 12x8 L brackets - **sold separately**

Control System

- Standard Infrared (IR) and Optional ZR800D IR Universal Learning Remote system
- Standard Radio Frequency (RF) remote control operates screen from 100 feet away
- Low-voltage detachable 3-way wall switch for in-line control
- Extended IR "eye" sensor for in-ceiling Infrared operation
- Built-in 5-12 volt trigger port (RJ-45) enables Drop/Rise operation to synchronize with the projector's power cycle
- Optional ZR800D IR Universal Remote Control, wireless 5-12 volt trigger, Universal 5-12 volt trigger (for projectors that don't have a trigger output port) and In-wall switch - **sold separately**

