

**Elite Screens Motor Specifications Table (220V)**

Model	Type	Products used in	Motor Diag. (cm) / (in)	Torque	RPM	Db	Output Torque	Output Speed	Output Current	Voltage	Power	Frequency	Tube Diameter	Running Time	Tube Length	Insulation Class	Protection Index
ES35-6-14 (Tubular)	Tubular Motor	Yard Master Electric Series, Home Series 120" and above, TE92V, TE85C, TE84, VMAX 135" (included) - VMAX180" (included), Spectrum 2 Series, Evanesce Tab-Tension B and Evanesce B Series, Saker Series SK135-E6 and above (Ver.2), Saker Tab-Tension Series SKT135-E6 and above (Ver.2), SKT135H-E12-AUHD,	3.5/1.38	6	14	48db	6Nm	14 rpm	0.43 A	AC220V	95 watt	50Hz	35 mm	4 min.	405 mm	F	IP44
ES35-3-28 (Tubular)		Home Series 100" and below	3.5/1.38	3	28	48db	3Nm	28rpm	0.43A	AC220V	95 watt	50Hz	35mm	4 min.	405 mm	F	IP44
ES45-50-12 (Tubular)		VMAX265"and above	4.5/1.78	50	12	48db	50Nm	12r/min	1.13A	220V	250 watt	50Hz	45mm	5 min.	600mm	F	IP44
ES45-10-17 (Tubular)		Kestrel, Merlin Series, Merlin Tab- Series, Merlin Module Series, Merlin Module Tab-Tension Series	4.5/1.78	10	17	48db	10Nm	17r/min	0.64A	220V	140 watt	50Hz	45mm	5 min.	500mm	F	IP44
ES45-8-30 (Tubular)		Osprey Dual Tension Series 117" and below, CineTension Series TE120"(included)-TE92H(included), Evanesce, Evanesce Tab-Tension In-Ceiling Screen, Evanesce Plus 180" and below	4.5/1.78	8	30	48db	8Nm	30r/min	0.64A	220V	140 watt	50Hz	45mm	5 min.	500mm	F	IP44
ES45-15-30 (Tubular)		Osprey Dual Tension Series 120" and above(DTE), CineTension 120"above, VMAX series 200"(included)-235" (included), Evanesce Plus Series 200"	4.5/1.78	15	30	48db	15Nm	30r/min	0.86A	220V	190 watt	50Hz	45mm	5 min.	600mm	F	IP44
Synchronous MotorB	Synchronous Motor	VMAX135" below, VMAX136S, Spectrum Series 128" and below, Electric136S, Spectrum Tab-Tension series, Saker series SK135-E12 and below, Saker Tab-Tension series SKT135-E6 and below	6/2.36	n/a	n/a	46db	17Kg/cm	15r/min	0.17A	220V	38 watt	50Hz	60mm	n/a	60mm	E	n/a