











Evanesce Tab-Tension CineGrey 5D® | J Type vs. M Type Comparison

Series Name	Evanesce Tab-Tension CineGrey 5D - Evanesce Tab-Tension CineGrey 5D®	
	J Type	M Type
Product Picture		
Screen Material	CineGrey 5D®	
Aspect Ratio - Diagonal Sizes	16:9 - 106"/126"	
4 Side Black Masking Borders	Yes	
Seamless	Yes	
GREENGUARD® Certified	Yes	
ISF® Certified	Yes	
Design and Installation		
Case picture		
Opening visible when screen retracts	Yes	No
Case Description	Aluminum White	
Case Dims - LxWxH	106 model = 112.2"x7.3"x6.1"	106" model = 105.3"x3.9"x4.6"
	126 model = 129.7"x7.3"x6.1"	126" model = 127.4"x3.9"x4.6"
Installation Method/Type	In-ceiling Recessed (concealed)	
Sliding/Moveable installation bars	No - Fixed points at ends only 	Yes - Suspension brackets permit bars to slide on top of case 
Detachable IEC power cable	Yes	No
Hardwire required	No, standard 3-prong power cable	
Control System		
Control Kit Picture		
Infrared Remote	Yes	
Radio Frequency Remote	Yes	
3-way wall switch keypad	No	Yes
IR "eye" extended sensor	Yes	
5-12 volt projector trigger capable	Yes - Wired only	Yes - Wired and Wireless
Wireless 5-12 volt projector trigger via RF remote	No	Yes, included
Accessories Connection Location	Inputs located on left end of screen  · IR "eye" extended sensor · 5-12 volt trigger · IEC power cord	RJ45 input located on circuit board box attached to power cable  RJ45 input for... · IR "eye" extended sensor · 5-12 volt trigger
Motor Type (speed)	Tubular (fast)	