Sable Frame StarBright 9® Series

Ceiling Ambient Light Rejecting Projection Screen




Compatible with Standard Throw Projectors ONLY

Product Description

The *Sable Frame StarBright 9®* provides reference grade video performance in either a dark room or rooms with high levels of interior lighting. Instead of the image washout common with typical matte-white projection screens, the Sable Frame StarBright 9® blocks illumination from overhead or off-axis light sources for a bold, bright, crystal-clear image even in the most challenging spaces. When shown under optimal cinematic lighting conditions, the material lives up to its ISF certification by the world-renowned Imaging Science Foundation. The projection surface is bordered by a 2.3" thick aluminum frame that is coated in hand-wrapped velvet.







Models	Diagonal	Aspect Ratio	View Width	View Height	Material	Gain	Frame Width
ER106H-SB9	106"	16:9	92.4 in	52.0 in	StarBright 9®	0.9	2.3 in
ER122H-SB9	122"	16:9	106.4 in	59.8 in	StarBright 9®	0.9	2.3 in
ER156C-SB9	156"	16:9	143.6 in	59.8 in	StarBright 9®	0.9	2.3 in

For full list of models visit www.elitescreens.com

Product Features

- StarBright 9 material has a wide viewing angle that reflects a bright image across the entire surface for superior off-axis performance
- Active micro-structural filters absorb 95% of ambient light from above and below
- Diffusion layers enhance color contrast and black/white dynamic range performance
- Wide diffusion uniformity across the entire screen surface without color shift, texture, shimmer, hot-spotting, dark corners and other distracting artifacts
- Scratch-resistant material is easy to clean
- Available in diagonal sizes: 106" and 122" in 16:9 or 156" in 2.40:1 aspect ratio

- ISF Certified for accurate color reproduction
- 4K/8K Ultra HD, HDR Ready for high resolution projectors and content
- 2.3" wide aluminum frame with hand-wrapped velveteen surface provides an elegant finish while absorbing projector overshoot
- Spring and grommet attachment system allows for an easy installation with a clean, smooth projection surface
- Lightweight split-frame design is cost effective for shipping and provides easy access to install sites
- Assembles and installs in minutes
- Sliding wall mounts ensure precision on-axis alignment
- 2-Year / 3-Year ENR-G Manufacturer's Warranty by Elite Screens