













### Starling Tab-Tension 2 CineGrey 5D® | J Type vs. M Type Comparison

Series Name	Starling Tab-Tension 2 CineGrey 5D® - J Type	Starling Tab-Tension 2 CineGrey 5D® - M Type
Product Picture		
Screen Material	CineGrey 5D®	
Aspect Ratio - Diagonal Sizes	16:9 - 92"/106"/120"/135"	
4 Side Black Masking Borders	Yes	
Seamless	Yes	
GREENGUARD® Certified	Yes	
ISF® Certified	Yes	
<b>Design and Installation</b>		
Case picture		
Case Description	Aluminum - Black	
Case Dims - LxWxH	92" model = 100.4"x4.5"x5.3"	92" model = 92.5"x4.4"x4.3"
	106" model = 112.8"x4.5"x5.3"	106" model = 111.5"x4.4"x4.3"
	120" model = 125"x4.5"x5.3"	120" model = 124"x4.4"x4.3"
	135" model = 138.2"x4.5"x5.3"	135" model = 137"x4.4"x4.3"
Installation Method/Type	Flush wall/ceiling or Ceiling Suspended	
Installation Brackets Included for Flush/Wall Installation and eyebolts for suspended installation	 Yes  Yes	 Yes  Yes
Detachable IEC power cable	Yes	No
Hardwire required	No, standard 3-prong power cable	
<b>Control System</b>		
Control Kit Picture		
Infrared Remote	Yes	
Radio Frequency Remote	Yes	
3-way wall switch keypad	No	Yes
IR "eye" extended sensor	Yes	
5-12 volt projector trigger capable	Yes - Wired only	Yes - Wired and Wireless
Wireless 5-12 volt projector trigger via RF remote	No	Yes, included
Accessories Connection Location	Inputs located on left end of screen <ul style="list-style-type: none"> <li>· IR "eye" extended sensor</li> <li>· 5-12 volt trigger</li> <li>· IEC power cord</li> </ul> 	RJ45 input located on left side of case (bottom) RJ45 input for... <ul style="list-style-type: none"> <li>· IR "eye" extended sensor</li> <li>· 5-12 volt trigger</li> <li>· 3-way wall switch</li> </ul> 
Motor Type (speed)	Tubular (fast)	